NEWS AND INFORMATION

LED RetroFit 2'x2' Troffers



RetroFit It, and Forget It.

Litetronics presents LED RetroFit - the first fluorescent troffer retrofit solution designed for quick and easy installation. Powerful, rare earth magnets secure the retrofit to the existing housing, allowing for hands-free installation. In less than the time needed to change a ballast, you can convert your existing fixture into energy-saving LED that lasts up to 20 years. Leave it to Litetronics to create the easiest way to convert to energy-saving LED; protecting the environment and lowering your operating costs for years to come.

Benefits

- 85,000-hour rated life; 7-year warranty
- Installs in minutes
- No need to break into the ceiling plenum
- Universal 120-277V driver
- Designed to preserve the optical output and asthetics of your fixture
- Shatterproof; safe for food service applications

Markets & Applications

- Restaurants
- Retail
- Schools
- Hospitals
- Office Lighting





235 East 171st Street Harvey, IL 60426 www.Litetronics.com

LED RetroFit 2x4' Troffer Retrofit

Features and Benefits

- 85,000-hour life
- 7-year warranty





| ТҮРЕ | WATTS | VOLTS | DESCRIPTION | ORDERING CODE | AVERAGE RATED LIFE* | CRI | POWER FACTOR | CCT (K) | RETROFIT LUMENS** | LUMINAIRE LUMENS** |
|-------------|-------|---------|---------------------------|---------------|------------------------|-----|-----------------|---------|----------------------|-----------------------|
| 2X2, 3-LAMP | 32 | 120-277 | 32W 2X2-3 LED RF QC 3500K | RF32UQT235 | 85,000H | 83 | >.95 | 3500 | 3,600 | 3,100 |
| | 32 | 120-277 | 32W 2X2-3 LED RF QC 4000K | RF32UQT240 | 85,000H | 83 | >.95 | 4000 | 3,600 | 3,100 |
| | 32 | 120-277 | 32W 2X2-3 LED RF QC 5000K | RF32UQT250 | 85,000H | 83 | >.95 | 5000 | 3,600 | 3,100 |

Energy Saving Solution - 2'x2' - Two T8 U-Bend Lamps¹

| Present Wattage | | 56.3W ² | |
|---|--------------------------|--|--|
| x Annual Operating Hours | 4,380 hrs. | | |
| | = | 246,594 watt-hours | |
| ÷ 1,000 | = | 246.59 kWh per year | |
| x kWh rate of \$0.12 | = | \$29.59 per year | |
| x 125 fixtures | = | \$3,698.75 annual energy cost per space ³ | |
| | | | |
| New Wattage | | 32 W | |
| x Annual Operating Hours | | 4,380 hrs. | |
| | = | 140,160 watt-hours | |
| ÷ 1,000 | = | 140.16 kWh per year | |
| x kWh rate of \$0.12 | = | \$16.82 per year | |
| x 125 fixtures = | | \$2,102.50 annual energy cost per space | |
| Total Estimated Energy Savings ¹ | \$1,596.25 (43% Savings) | | |

¹Based on two 32 watt T8 u-bend lamps

Candlepower

| Allyle | | 77 | 70 |
|--------|------|------|------|
| 0 | 1365 | 1365 | 1365 |
| 5 | 1363 | 1360 | 1355 |
| 10 | 1348 | 1342 | 1333 |
| 15 | 1322 | 1312 | 1296 |
| 20 | 1281 | 1267 | 1244 |
| 25 | 1233 | 1207 | 1175 |
| 30 | 1147 | 1126 | 1089 |
| 35 | 1067 | 1028 | 984 |
| 40 | 978 | 913 | 860 |
| 45 | 861 | 776 | 718 |
| 50 | 719 | 652 | 571 |
| 55 | 568 | 525 | 452 |
| 60 | 418 | 376 | 353 |
| 65 | 301 | 250 | 273 |
| 70 | 228 | 165 | 208 |
| 75 | 182 | 120 | 152 |
| 80 | 137 | 100 | 112 |
| 85 | 75 | 58 | 61 |
| 90 | 0 | 0 | 0 |
| | | | |

Light Distribution

| Degress | Lumens | %Luminaire |
|---------|--------|------------|
| 0-30 | 1049 | 32.4 |
| 0-40 | 1686 | 52.1 |
| 0-60 | 2741 | 84.7 |
| 0-90 | 3236 | 100 |

Spacing Criterion

| Spacing Criterion [0-180] | 1.26 | |
|------------------------------|------|--|
| Spacing Criterion [90-270] | 1.20 | |
| Spacing Criterion [Diagonal] | 1.30 | |











^{* 85,000} hours based on 35°C ambient room temperature

^{**} Based on Photometric testing consistent with IES LM-79 testing; Lumens will vary based on diffuser and fixture

¹Dual connectors for multi-channel operation; allows center tube to be operated independantly

² Based on a .88 ballast factor

³ Based on 125 fixtures per space, operating 4,380 hours a year. 125 fixtures is roughly equivalent to a 10,000 square foot space. kWh rates will vary.

^{*} Patent Pending